

Applicant : Ronald P. Knockeart et al.

Attorney Docker 09650-005008 / 2003P11514US

Serial No. : 10/656,381

Filed : September 5, 2003

Page : 2 of 8

Please amend the claims as follows (this listing of claims replaces all prior listings):

1-21. (Cancelled)

22. (Currently amended) A method for detecting when a vehicle deviates from a planned route comprising:

tracking a first estimated position of the vehicle using signals from a positioning system that are received at the vehicle;

tracking a second estimated position of the vehicle using an estimate of ~~[[the]]~~ a distance traveled along and the planned route, wherein the planned route includes a first point along the route and a path along the route following the first point, and wherein tracking the second estimated position includes detecting when the vehicle is at the first point on the planned route, ~~[[and]]~~ estimating ~~[[the]]~~ a distance traveled along the path following after detecting the vehicle is at the first point, and determining the second estimated position according to a position along the planned route at the estimated distance on the path following the first point; and

detecting that the vehicle has deviated from the planned route when the first estimated position and the second estimated position differ by at least a tolerance distance.

23. (cancelled)

24. (Currently amended) The method of claim 22 further comprising adjusting the tolerance distance, including reducing the tolerance distance when the vehicle is detected to be at the first point on the planned route, and increasing the tolerance distance as the vehicle travels ~~along the path~~ following the first point.

25. (Currently amended) Software recorded on a computer readable medium for causing an in-vehicle computer to perform the functions of:

Applicant : Ronald P. Knockeart et al.
Serial No. : 10/656,381
Filed : September 5, 2003
Page : 3 of 8

Attorney Docket 09650-005008 / 2003P11514US

tracking a first estimated position of a vehicle using signals from a positioning system that are received at the vehicle;

tracking a second estimated position of the vehicle using an estimate of ~~[[the]]~~ a distance traveled ~~along and~~ the planned route, wherein the planned route includes a first point along the route and a path along the route following the first point, and wherein tracking the second estimated position includes detecting when the vehicle is at the first point on the planned route, ~~[[and]]~~ estimating ~~[[the]]~~ a distance traveled ~~along the path following after detecting the vehicle is at the first point, and determining the second estimated position according to a position along the planned route at the estimated distance on the path following the first point; and~~

detecting that the vehicle has deviated from the planned route when the first estimated position and the second estimated position differ by at least a tolerance distance.

26. (Currently amended) A vehicle tracking system comprising:

a first position estimator including a positioning system receiver, for determining a first estimate of the vehicle's location determined using information received from the positioning system receiver;

storage for a planned route;

a second position estimator coupled to a vehicle motion sensor and to the storage for the planned route, for determining a second estimate of the vehicle's location using information received from the vehicle motion sensor and the planned route, wherein the planned route includes a first point along the route and a path along the route following the first point, and wherein tracking the second estimated position includes detecting when the vehicle is at the first point on the planned route, ~~[[and]]~~ estimating the distance traveled ~~along the path following after detecting the vehicle is at the first point, and determining the second estimated position according to a position along the planned route at the estimated distance on the path following the first point; and~~

Applicant : Ronald P. Knockeart et al.
Serial No. : 10/656,381
Filed : September 5, 2003
Page : 4 of 8

Attorney Docket 09650-005008 / 2003P11514US

an off-route detector coupled to the first position estimator and to the second position estimator, for comparing the first estimate of the vehicle's position and the second estimate of the vehicle's position.

27. (New) The software of claim 25, further causing an in-vehicle computer to perform the functions of adjusting the tolerance distance, including reducing the tolerance distance when the vehicle is detected to be at the first point on the planned route, and increasing the tolerance distance as the vehicle travels following the first point.

28. (New) The vehicle tracking system of claim 26 in which the off-route detector indicates that the vehicle has deviated from the planned route when the first estimate and the second estimate differ by at least a tolerance distance.

29. (New) The vehicle tracking system of claim 28 in which the off-route detector reduces the tolerance distance when the vehicle is detected to be at the first point on the planned route, and increases the tolerance distance as the vehicle travels following the first point.